INTERNATIONAL JOURNAL OF ELECTRONICS AND COMPUTER APPLICATIONS



ORIGINAL ARTICLE

Article access online



© OPEN ACCESS Received: 11.08.2024 Accepted: 22.11.2024 Published: 12.12.2024

Citation: Kakkar M, Vinoy P, Deshpande S, Tarfe S. (2024). LV Battery Charging and Fault Detection. International Journal of Electronics and Computer Applications. 1(2): 32-35. https://doi. org/10.70968/ijeaca.v1i2.2

* Corresponding author.

munmun.kakkar@dypiemr.ac.in

Funding: None

Competing Interests: None

Copyright: © 2024 Kakkar et al. This is an open access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

ISSN

Print: XXXX-XXXX Electronic: 3048-8257

LV Battery Charging and Fault Detection

Munmun Kakkar^{1*}, Parthiv Vinoy², Shridhar Deshpande², Sudhanshu Tarfe²

 Assistant Professor, Department of Electronics & Communication Engineering, Dr. D. Y. Patil Institute of Engineering, Management and Research, Pune, 411044, Maharashtra, India
Student, Department of Electronics & Communication Engineering, Dr. D. Y. Patil Institute of Engineering, Management and Research, Pune, 411044, Maharashtra, India

Abstract

Low-voltage (LV) battery systems are integral components in a variety of applications such as portable electronics, automotive electronics, renewable energy, and non-interruptible electronics. Effective charging and early detection of dead batteries are crucial to improve its performance, safety, and lifespan. This research addresses the challenges associated with LV battery charging and fault detection. The study investigates fault detection and diagnosis methods to identify issues such as cell degradation, thermal runaway, overcharging, and short circuits. These fault detection mechanisms employ various sensing technologies, including voltage and current monitoring, temperature sensing, impedance spectroscopy, and machine learning-based approaches. The integration of these charging and fault detection technologies enhances the reliability, safety, and overall performance of LV battery systems. This research contributes to the development of sustainable and resilient energy solutions, benefiting a variety of businesses and applications. It paves a way for efficient & intelligent LV battery management systems, ensuring the continued growth and adoption of battery-powered devices and electric vehicles in the modern world.

Keywords: Low-voltage (LV) battery; Battery management systems; Cell degradation; Overcharging; Impedance spectroscopy

Introduction

Concerning environmental pollution, the association with automobiles is undeniable. Traditional fossil-fuel vehicles have contributed significantly to environmental issues, including the greenhouse effect and air pollution. Consequently, there is a growing global shift towards embracing new energy vehicles, particularly electricpowered vehicles, which are poised to become a prevailing trend in the future. Currently, nations worldwide are actively engaged in research and development related to electric-powered vehicles. It is widely recognized that effective battery management stands out as a pivotal challenge in advancing the electric vehicle industry. The need for supplementary hardware installations and the integration of Battery Management Systems (BMS) is particularly critical in this endeavour. More BMS units have been incorporated, enhancing functionalities like equalization management and fault diagnosis. A diverse range of algorithms is employed to ensure accuracy and reliability in these estimations. In the context of electric vehicles, the State of Charge (SOC) of batteries holds a role akin to the fuel gauge in traditional internal combustion engine vehicles. Its primary function is to communicate the current battery charge level to the driver. Simultaneously, it serves to prevent issues such as overcharging and over-discharging, which can be detrimental to battery health and safety.

In the context of Low Voltage (LV) battery systems, the detection and management of overvoltage and overcurrent events are critical for ensuring the safe and efficient operation of the battery. LV batteries control a wide extend of applications, counting EVs, renewable vitality frameworks, reinforcement control supplies and convenient gadgets. Overvoltage and overcurrent issues can lead to battery damage, reduced lifespan, safety hazards, and operational inefficiencies. Therefore, the problem at hand is to develop a robust system for the detection and mitigation of overvoltage and overcurrent conditions in LV battery systems.⁽¹⁻⁵⁾.

Methodology

State of charge

State of Charge (SoC) is a term used to describe the current level of charge or energy remaining in a rechargeable battery, typically expressed as a percentage of the battery's total capacity. SoC provides valuable information about the available energy in the battery at a specific point in time and is a critical parameter in battery management and power systems. It is used to gauge how much energy is left for a battery-powered device or system. For example, if a battery is at 50% SoC, it means that it currently contains half of its full capacity, and therefore, it has approximately half of its energy available for use. SoC can be determined through various methods, including voltage measurements, coulomb counting, & more advanced techniques involving battery management systems that take into account factors like temperature, discharge and charge rates, and the battery's internal resistance. Accurate SoC monitoring is essential for efficient battery utilization, as well as for preventing overdischarging (which is harmful for the battery) and managing power resources effectively.

$$SOC = \frac{Q_c}{Q} \times 100\% = 100\% - \frac{Q_e}{Q}. \label{eq:soc}$$

Estimation of state of charge

Several methods are used for estimating SoC:

Open-Loop Methods (Voltage-Based): These methods estimate SoC without direct measurements of current. They rely on the voltage of the battery, which can be a less accurate method but is simple and widely used.

Voltage vs. Capacity: This method uses a voltage to -SoC mapping based on a discharge/charge curve specific to the battery type. It relates the battery voltage to the known capacity at different states of charge.

Circuit Diagram



Outcomes

Detection of over voltage

Overvoltage refers to a condition where the voltage in an electrical circuit or system exceeds its intended or designed level. This excess voltage can be temporary or sustained and can occur by a variety of factors such as power surges, lightning strikes, equipment malfunctions, or improper operation of power systems. Overvoltage can potentially lead to damage to electronic devices, equipment, and electrical systems, as well as pose safety risks to individuals working with or near the affected circuits. Protecting against overvoltage conditions is essential to make certain the proper functioning and durability of electrical and electronic systems.

Detection of over current

Overcurrent, in the context of electrical engineering and circuits, is a situation where the current flowing through a conductor or component exceeds its intended or designed limit. This can be due to various factors, such as excessive load, short circuits, faulty components, or other anomalies in an electrical system. Overcurrent can potentially lead to equipment damage, overheating, electrical fires, and safety hazards. To prevent these risks, protective devices like fuses, circuit breakers, and relays are used to detect and respond to overcurrent conditions by interrupting the flow of electricity or taking other protective actions.

Battery Status

Battery status refers to the condition or state of a battery, which is typically used to power electronic devices or store electrical energy. It gives data about the battery's current charge level, capacity and overall status. Battery status information is crucial for users and device management systems to ensure that devices have sufficient power and to monitor the condition of the battery. Battery status is essential for users to manage the power needs of their devices and to make informed decisions about when to charge, replace, or maintain batteries. In many cases, modern electronic devices and operating systems provide detailed battery status information to ensure efficient use and prolong the life of batteries.

Efficiency

The efficiency of low voltage batteries refers to their ability to convert input energy during charging into stored energy and then release that stored energy during discharge with minimal losses. This performance is important for maximizing the performance and lifespan of the battery, in addition to minimizing power waste. Efficiency is influenced by various factors including battery chemistry, temperature, charge/discharge rate, depth of discharge, and the presence of battery management systems. Lithium-ion batteries, for example, exhibit higher efficiency when compared to lead-acid batteries due to their lower internal resistance and higher energy density. To ensure optimal efficiency, its essential to use proper charging and discharging techniques, maintain appropriate operating conditions, and integrate efficient battery management systems. Periodic maintenance and monitoring are necessary to identify and address any issues that may affect efficiency over time.

Overheating

Overheating of low voltage batteries poses significant safety risks and can result from various factors. When a battery operates beyond its encouraged temperature range, it could lead to thermal runaway, a self-reinforcing reaction causing rapid heat generation and potentially resulting in fire or explosion. Common causes include overcharging, high discharge rates, external heat sources, poor ventilation, internal short circuits, overuse, and age-related degradation. Prevention measures include using proper charging equipment, avoiding high discharge rates, ensuring adequate ventilation, inspecting batteries for damage, and implementing thermal management systems. Minimizing the risk of overheating is crucial for maintaining safety and prolonging battery lifespan.

Output



Conclusion

In conclusion, low-voltage (LV) battery charging, and fault detection are crucial aspects of maintaining the reliability,

safety, and performance of battery-powered systems. The successful management of LV battery charging, and the early detection of faults play a pivotal role in a wide variety of applications, such as electric vehicles, portable electronics, renewable energy systems, and more.

References

- Zhang Y, Li T, Yan X, Wang L, Zhang J, Diao X, et al. Electric Vehicle Charging Fault Monitoring and Warning Method Based on Battery Model. *World Electric Vehicle Journal*. 2021;12(1):1–15. Available from: https://doi.org/10.3390/wevj12010014.
- 2) Zhang M, Fan X. Review on the State of Charge Estimation Methods for Electric Vehicle Battery. *World Electric Vehicle*. 2020;11(1):1–17. Available from: https://doi.org/10.3390/wevj11010023.
- 3) Shi J, Tian M, Han S, Wu TY, Tang Y. Electric vehicle battery remaining charging time estimation considering charging accuracy and charging profile prediction. *Journal of Energy Storage*. 2022;49. Available from: https://dx.doi.org/10.1016/j.est.2022.104132.
- Wu W. Charging time estimation and study of charging behavior for automotive Li-ion battery cells using a Matlab/Simulink model. Sweden. 2016. Available from: https://www.diva-portal.org/smash/get/diva2: 1040690/FULLTEXT01.pdf.
- Khaneghah MZ, Alzayed M, Chaoui H. Fault Detection and Diagnosis of the Electric Motor Drive and Battery System of Electric Vehicles. *Machines*. 2023;11(7):1–33. Available from: https://doi.org/10.3390/ machines11070713.